9	EPA
---	------------

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

SITE NUMBER (to be assigned by Hq) REGION 6 LA01317

GENERAL INSTRUCTIONS: Complete Sections I and III through XV of this form as completely as possible. Then use the informa-

File. Be sure to include all approtection Agency; Site Tracking Sys	priate Supplemental Reports in	the file.	Submit a copy of the	forms to: U.S.	Environmental Pro	0-
	I. SITE IDE	NTIFICAT	ION			
A. SITE NAME (Forme)	rly a division of		T (or other identifier)			
DELTA SHIPYARD	Delta Ironworks)		strial Blyd.			
C. CITY		D. STATE		F. COUNTY N		
Houma G. SITE OPERATOR INFORMATION		LLA	70360	Terreboni	ne Parish	
LININE				1 2. TELEPHO	NE NUMBER	
Raiph Arceneaux	, Vice President			(504)868-	-7450	
3. STREET	4. CITY			5. STATE	6. ZIP CODE	
Industrial Blvd	Houma			LA	70360	
1	if different from operator of site)			1		
I TOTAL TOTA	sident, Delta Servic	es Indu	stries	(504)868	3-7450	
Houma (P. O. Box 10				4. STATE	S. ZIP CODE	
I. SITE DESCRIPTION			or or many constraints	LA	70361	
See Attachment "A"	en municipal de la companya de la co					
1. FEDERAL 2. STA	TE 3. COUNTY	4. MUNICI	PAL X 5. PRIV	ATE		
	II. TENTATIVE DISPOSITIO	N (comple	te this section last)	***		
A. ESTIMATE DATE OF TENTATIVE	B. APPARENT SERIOUSNES	S OF PRO				
DISPOSITION (mo., day, & yr.)	1. HIGH	2. MEDIUN	3. LOW	4. NOI	NE	
C. PREPARER INFORMATION				3. DATE (mo	dou to us)	
Deborah Vaughn		AND THE PROPERTY OF THE PARTY O	42-4521	3/11/8	The state of the s	
	III. INSPECTIO	N INFORM	ATION			
A. PRINCIPAL INSPECTOR INFORMA		2. TITLE				
Deborah A. Vaughn De	back a Vallet	FIT, G	eologist _	4. TELEPHO	NE NO. (area code &	& no.)
Ecology & Environment,				The second secon	and the state of t	
B. INSPECTION PARTICIPANTS	Ther, 1005 It. Halli,	04100	75201	(-, , , , , , ,		
1, NAME	2. ORGA	NIZATION		3. TE	LEPHONE NO.	
						7 1
Gordon Duncan	Ecology & Environm	ent		(214)742	2-4521	
				Clark	h=0 ./. /	
ar a constant and a c				Zas	058 475419	1
C. SITE REPRESENTATIVES INTER	VIEWED (corporate officials, work	cers, resider	nts)			
1, NAME	2. TITLE & TELEPHONE NO	э.		3. ADDRESS		
Lasa Tauna	President	Tio	duatoial Plud	Houma I	A 70260	
Leon Toups	(504)868-7450 Exec. Vice Preside		dustrial Blvd ta Svcs.	., Houlia, i	_A 70300	
Louis E. Talbot	(504)868-7450	nc, per	11 II	п	11	
Ralph Arceneaux	Vice President (504)868-7450		п	11	п	
Chuda Oldudau	Engineer, Delta Sh	ipyard	п	SUPERF " FILE		
Chris Olivier	(504)868-7450			TILL		-
13-				APR 3 0	1002	
				ATT OU	1332	
				- READOAN	HTEN	
EPA Form T2070-3 (10-79)	PAG	E 1 OF 10		HEONG CON	tinue On Reverse	

REVIEWED BY (6ASASC): X Solar

Continued From Page 2									
		IV. SAMF	LING INFOR	MA	ATION (continued)				
C. PHOTOS 1. TYPE OF PHOTOS			t a BHOTOSIN		USTODY OF: EDA Pagion	V T	(see attached photo		
and the growth of the second o									
D. SITE MAPPED?	RIA								
	OF	_{MAPS:} EPA Reg	ion VI (s	ee	e attached map and sk	eto	ches)		
E. COORDINATES									
1. LATITUDE (degminsec.)				2	. LONGITUDE (degminsec.)				
29 ⁰ 34'02" N				ļ	90 ⁰ 42'18" W				
			V. SITE INFO	R	MATION				
A. SITE STATUS									
1. ACTIVE (Those inductrial municipal sites which are being u for waste treatment, storage, or di on a continuing basis, even if infr quently.)	spos	2. INACTIV sites which no i wastes.)		1	3. OTHER(specify): (Those sites that include such inci where no regular or continuing use has occurred.)				
B. IS GENERATOR ON SITE? 1. NO X 2. YES(si	eci	ly generator's four-d	igit SIC Code):	37	731, 3732				
C. AREA OF SITE (in acres)		D. ARE THERE	BUILDINGS O	N	THE SITE?		***************************************		
		1, NO	X 2. YES(s	pe	cify):				
Approx. 40									
					OF SITE ACTIVITY				
Indicate the major site activity(and details relati			ity by marking 'X' in the approp	oriat	e boxes.		
A. TRANSPORTER	Χ,	8. STOR		' X '	C. TREATER	<u> </u>	D. DISPOSER		
1.RAIL		1.PILE			1. FIL TRATION		I. LANDFILL		
2.5HIP	Ţχ	2. SURFACE IMPO	UNDMENT		2. INCINERATION	2	2. LANDFARM		
3. BARGE	_	3. DRUMS			3. VOLUME REDUCTION	3	3.OPEN DUMP		
X 4. TRUCK	LX.	4. TANK, ABOVE	GROUND	X	4. RECYCLING/RECOVERY		4. SURFACE IMPOUNDMENT		
5. PIPELINE	 _	5. TANK, BELOW			5. CHEM./PHYS./TREATMENT		5. MIDNIGHT DUMPING		
6.OTHER(specify):	-	6.OTHER(specify)):	_	6. BIOLOGICAL TREATMENT		S. INCINERATION		
1	-		į		7. WASTE OIL REPROCESSING		OUNDERGROUND INJECTION S.OTHER (specify):		
	ł				8. SOLVENT RECOVERY	`	. OTHER(specify):		
			ļ		9.OTHER(specify):				
	İ				-				
E. SUPPLEMENTAL REPORTS: 1	the	site falls within an	y of the categor	ries	s listed below, Supplemental Repor	ts m	ust be completed. Indicate		
which Supplemental Reports you	have	filled out and attac	ched to this for.	••					
1. STORAGE	2. 11	CINERATION [3. LANDFIL	٠.	A SURFACE	5. (DEEP WELL		
6. CHEM/BIO/ 7. LANDFARM B. OPEN DUMP 9. TRANSPORTER 10. RECYCLOR/RECLAIMER									
		VII. WA	STE RELAT	ED	INFORMATION				
A. WASTE TYPE		_			_				
1. LIQUID	2. S	OLID [3. SLUDGE		4. GAS				
B. WASTE CHARACTERISTICS	_								
1. CORROSIVEX	2. 1	GNITABLE [3. RADIOAC	TI	VE 🕅 4. HIGHLY VOLATILE				
5. TOXIC	6. F	EACTIVE	7. INERT		8. FLAMMABLE				
9. OTHER(specify): C. WASTE CATEGORIES									
1. Are records of wastes available	re re	cords are ke	manifests, invent	6 (eu	tones, etc. below. shipyard office.				

Continued From Page 4
VIII. HAZARD DESCRIPTION (continued) B. NON-WORKER INJURY/EXPOSURE
E. B. RON-BORREN INJURI/EXPOSURE
C. WORKER INJURY/EXPOSURE
D. CONTAMINATION OF WATER SUPPLY
E. CONTAMINATION OF FOOD CHAIN
L. CONTAINING TON FOOD CHAIN
X F. CONTAMINATION OF GROUND WATER Contamination of ground water could occur due to infiltration of oil contaminated
waters generated in the cil/water senaration process. This contamination should be
waters generated in the oil/water separation process. This contamination should be minimal because soil permeabilities at the site are very low (10 to 10 cm/sec). See Attachment "C". Sampling of monitoring wells would determine whether contami-
See Attachment "C". Sampling of monitoring wells would determine whether contami-
nation has occurred.
G. CONTAMINATION OF SURFACE WATER

VIII. HAZARD DESCRIPTION (continued)	
N. FIRE OR EXPLOSION	
O. SPILLS/LEAKING CONTAINERS/RUNOFF/STANDING LIQUID	
Last of St. Last of Last of the Last of th	•
P. SEWER, STORM DRAIN PROBLEMS	
[] Q. EROSION PROBLEMS	
R. INADEQUATE SECURITY	
S. INCOMPATIBLE WASTES	

Continued From Page 6

Continued From Page 8 X. WATER AND HYDROLOGICAL DATA (continued) H. LIST ALL DRINKING WATER WELLS WITHIN A 1/4 MILE RADIUS OF SITE NON-COM-MUNITY (mark 'X') COMMUN-1. WELL 2. DEPTH (specify unit) 3. LOCATION (proximity to population/buildings) (mark 'X') None I. RECEIVING WATER X 3. STREAMS/RIVERS 2. SEWERS Houma Navigation Canal ___ 4. LAKES/RESERVOIRS 5. OTHER(specify): 6. SPECIFY USE AND CLASSIFICATION OF RECEIVING WATERS Fish, wildlife and other aquatic and semi-aquatic life, secondary contact recreations. Part of the Terrebonne Watershed. XI. SOIL AND VEGITATION DATA LOCATION OF SITE IS IN: ___ A. KNOWN FAULT ZONE B. KARST ZONE C. 100 YEAR FLOOD PLAIN D. WETLAND X E. A REGULATED FLOODWAY G. RECHARGE ZONE OR SOLE SOURCE AQUIFER F. CRITICAL HABITAT XII. TYPE OF GEOLOGICAL MATERIAL OBSERVED Mark 'X' to indicate the type(s) of geological material observed and specify where necessary, the component parts. C. OTHER (specify below) A. CVERBURDEN B. BEDROCK (specify below) 1. SAND X Quaternary Terrace & Alluvial Deposits 2. CLAY Χ 3. GRAVEL XIII. SOIL PERMEABILITY ___ A. UNKNOWN B. VERY HIGH (100,000 to 1000 cm/sec.) C. HIGH (1000 to 10 cm/sec.) D. MODERATE (10 to .1 cm/sec.) E. LOW (.1 to .001 cm/sec.) X F. VERY LOW (.001 to .00001 cm/sec.) G. RECHARGE AREA X 1. YES ___ 2. NO 3. COMMENTS: Only in that it is a coastal wetland. DISCHARGE AREA X 1. YES ___ 2. NO 3. COMMENTS: Only in that it is a coastal wetland. SLOPE 2. SPECIFY DIRECTION OF SLOPE, CONDITION OF SLOPE, ETC. 1. ESTIMATE % OF SLOPE 0 - ,5% J. other geological data South See Attachment "C"

INSTRUCTION STORAGE FACILITIES SITE INSPECTION REPORT Answer and Explain (Sugplemental Report) as Necessary. 1. STORAGE AREA HAS CONTINUOUS IMPERVIOUS BASE ["] NO X YES 2. STORAGE AREA HAS A CONFINEMENT STRUCTURE [X] YES [] NO 3. EVIDENCE OF LEAKAGE/OVERFLOW (It "Yes", document where and how much ranoll is overflowing or leaking from containment) TYES X NO 4. ESTIMATE TYPE AND NUMBER OF BARRELS/CONTAINERS 5 above ground storage tanks for recycled oil. See photos 1 & 5. 5. GLASS OR PLASTIC STORAGE CONTAINERS USED (X) 40 6. ESTIMATE NUMBER AND CAPACITY OF STORAGE TANKS Approx. 100,000 gallons. 7. NOTE LABELING ON CONTAINERS Storage tanks are labeled with safety notices. 8. EVIDENCE OF LEAKAGE CORROSION OR BULGING OF BARRELS/CONTAINERS/STORAGE TANKS (If"Yes", document evidence. Describe location and extent of damage. Take PHOTOGRAPHS) ĽŽ NO YES 9. DIRECT VENTING OF STORAGE TANKS NO 10. CONTAINERS HOLDING INCOMPATIBLE SUBSTANCES (If "Yes", document evidence. Describe location and identity of hezardous waste. Take PHOTOGRAPHS.) YES X NO 11. INCOMPATIBLE SUBSTANCES STORED IN CLOSE PROXIMITY (II "Yes", document evidence. Describe location and identity of hazardous waste. Take PHOTOGRAPHS.) YES X NO 12. ADEQUATE CONTAINER WASHING AND REUSE PRACTICES 13. ADEQUATE PRACTICES FOR DISPOSAL OF EMPTY STORAGE CONTAINERS

Non-disposable storage containers.

□ NO

INSTRUCTION SURFACE IMPOUNDMENTS SITE INSPECTION REPORT Answer and Explain (Supplemental Report) as Necessary. 1. TYPE OF IMPOUNDMENT Two identical impoundments in filled marsh area. See photo #5. 2. STABILITY/CONDITION OF EMBANKMENTS Good. See photo #4. 3. EVIDENCE OF SITE INSTABILITY (Erosion, Settling, Sink Holes, etc.) TIYES XING 4. EVIDENCE OF DISPOSAL OF IGNITABLE OR BEACTIVE WASTE LL AER TYNO 5. ONLY COMPATIBLE WASTES ARE STORED OR DISPOSED OF IN THE IMPOUNDMENT X YES [NO 5. RECORDS CHECKED FOR CONTENTS AND LOCATION OF EACH SURFACE IMPOUNDMENT TYES V NO 7. IMPOUNDMENT HAS LINER SYSTEM 7a. INTEGRITY OF LINER SYSTEM CHECKED X NO (T) YES YES NO N/A 7b. FINDINGS Subsurface soils have permeability of 10^{-7} to 10^{-8} cm/sec. See Attachment "C". 8. SOIL STRUCTURE AND SUBSTRUCTURE Medium gray organic clay at surface to soft gray silty clay with sand traces at 40 to 50 feet. 9. MONITORING WELLS X YES TWO (2) wells installed. (See Attachment "C" - monitoring well logs.) 10. LENGTH, WIDTH, AND DEPTH LENGTH 75' (each) WIDTH 40' (each) DEPTH 5' (each) Two impoundments. 11. CALCULATEDQVOLUMETRIC CAPACITY 15,000 ft. 12. PERCENT OF CAPACITY REMAINING 30% 13. ESTIMATE FREEBOARD 1.5 ft. 14. SOLIDS DEPOSITION XII YES NO Low solids deposited. 15. CREDGING DISPOSAL METHOD Unknown 16. OTHER EQUIPMENT

ATTACHMENT A

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT SUPPLEMENT SHEET

Instruction - This sheet is provided to give additional information in explanation of a question on the form T2070-3.

Corresponding number on form

I, i.

Additional Remark and/or Explanation

Delta Ironwords was a large industrial park (approximate 165 acres) located on Industrial Blvd. in southeast Houma, LA. . The corporation of Delta Ironworks owned and operated 7 divisions, all located within the Delta Ironworks industrial facilities. These 7 divisions were:

(1) Delta Shipyard - repair and painting of ships.

(2) Delta Fabrication - produces offshore oil support equipment (platforms).

(3) Delta Construction - produces pipes.

(4) Delta Safety & Supply - distributes safety equipment and constructs fire safety equipment.

(5) Heldenbrand - inspection, repair and modification of drill pipes.

(6) Delta mud & chemical - distributor of drilling muds.

(7) Gemoco - construction of offshore oil drill support equipment.

In 1969, Delta Ironworks was sold to Chromalloy American Corp., St. Louis, MO. Chromalloy maintained all 7 divisions until 1980. In November 1980 Chromalloy sold 5 of the divisions to Delta Services Industries, keeping Delta Mud & Chemical and Gemoco.

At the present time the old Delta Ironworks (LA 01317) area houses the same 7 divisions listed above, but has two owners: (1) Delta Services Industries, Houma, LA and (2) Chromalloy American Corp., MO.


Upon inspecting the facilities, the FIT representatives found that only Delta Shipyard, owned by Delta Services Industries, may deal with hazardous wastes that could potentially pose a contamination problem.


Delta Shipyard consists of cleaning and repair facilities for small cargo and fishing vessels. Before any repair work may commence the vessels must be certified vapor free by the Coast Guard. The vessels are steam cleaned and the oily wastes are removed. The generated oils and waste waters are sent through a separation process after which the waste oil is recovered and sold. The wastes are stored in evaporation ponds (surface impoundments).

III, E.

Oily Wastes
M. K. Fuels, Inc., P. O. Box 2802, Baton Rouge, LA 70821, (504)343-4662, Oily Wastes

Clayton L. Holden, P.O. Box 151, Chalmette, LA. (no longer used because he refuses to handle a manifest), Oily Wastes J & L Oils, P. O. Box 209, Geismar, LA 70734, (504)673-6785,







SOIL TESTING ENGINEERS, INC. CONSULTING GEOTECHNICAL ENGINEERS

P. O. BOX 80379 • 316 HIGHLANDIA DRIVE • BATON ROUGE, LOUISIANA 70808 • PHONE (504) 292 - 4790

CNP BOUTWELL, JR. PHD B ADAMS, ME BAYANT, ME METH DERICK, MS FED PROFESSIONAL ENGINEERS

🕻 arown, MS

November 26, 1980

T. Baker Smith and Sons, Inc. Environmental Research Division P. O. Box 2266 Houma, Louisiana 70361

Attention: Mr. Horace J. Thibodaux, RS

Director of Environmental Research

Re: Preliminary Soil Borings and Laboratory Testing Delta Shipyard Disposal Pit Houma, Louisiana

File: 80-173

Gentlemen:

We have completed the field work and laboratory tests performed on samples obtained from two borings completed during the period November 3 and 4, 1980, at the Delta Shipyard disposal pit. Additionally, two observation wells with caps, were installed close to the borings (see Figure 2). The findings of the borings and the results of the laboratory testing are presented herein. The approximate locations of the borings are shown on the Boring Plan, Figure 1. The soil data on this cross section has been interpolated between the borehole locations and does not define continuity of the strata. For details, refer to the individual logs of the borings. The field and laboratory procedures used in this investigation are discussed below.

It should be noted that a geotechnical/geologic report was not requested at this stage. If such a report is later required, then necessary additional borings and testing, as well as engineering analyses can be performed.

FIELD EXPLORATION

General. The borings were made with tractor-mounted, rotary-type drilling equipment. Samples were obtained continuously in the upper 20 feet; below the 20 foot level, samples were generally obtained on 3 to 5 foot centers. The total exploration program consisted of 100 lineal feet of borings, 40 feet of which were sampled continuously. Logs of the borings are attached. The boreholes were grouted with a thick bentonite/cement grout. Two observation wells were installed as indicated on the Monitoring Well logs (W-1 and W-2) and Figure 1.

CONSULTATION - EXPLORATION - TESTING - INSPECTION

LAKE CHARLES OFFICE: 4001 LEGION STREET • LAKE CHARLES, LOUISIANA 70601 • PHONE (318) 433-6912

ATTACHMENT C

Sampling Procedures. In the cohesive and semi-cohesive soils, relatively undisturbed samples were secured using a 3 inch diameter, thin-wall Shelby Tube sampler. In this sampling procedure, the borehole is advanced to the desired level, and the tube is lowered to the bottom of the boring. It is then forced about 2 feet into the undisturbed soil in one continuous stroke. The tube is retrieved and the sample extruded by a hydraulic piston. The sample is then visually classified and a penetrometer relative strength test performed. Any disturbed portions are discarded, and the sample protected for transportation to the laboratory.

LABORATORY PROCEDURES

Some samples from the various strata were tested in the laboratory to determine their classifications and permeability characteristics. The samples and types of tests performed were selected by a geotechnical engineer. The testing program conducted is described below.

Classification Tests. Thirteen (13) Atterberg Limit Determinations, and one Separate Moisture Content Determination were conducted to classify the soil types.

Consolidation/Permeability Tests. Two (2) Standard Consolidation tests were performed. These were used in determining the Coefficient of Permeability of fine grained soils. The results are given below.

Boring	Depth	Perm. Coef.	Soil
No.	(feet)	(cm/sec.)	Description
B Ì	- 6-8	4.3×10^{-8}	Gray organic clay
B-1	12-14	1.2×10^{-7}	Dark gray organic clay (peat)

Chemical Tests. Fourteen (14) pH determinations were performed to determine soil acidity/alkalinity. The results are give on Table I.

The results of the consolidation test are presented on Figure A-I through A-II; the remainder of the testing program is summarized in the appropriate columns of the boring logs.

We will be happy to answer any questions which may arise concerning this information. It has been a pleasure to work with Mr. Thibodaux on this project, and we look forward to serving T. Baker Smith and Sons again in the future.

Sincerely,

Whoe

Marendra M. Dave And Project Engineer


Da Migricer

Richard B. Adams, P.E.

/11t

Enclosures

Copies submitted: (4)




SOIL PROFILE

No Horiz. Scale

NOTE:

Strata interpolated between a not define continuity between



No Scale

Project Delta Disposal Pit Houma, Louisiana

SOIL BORING LOG

Boring No. B-1

Client T. Baker Smith & Sons, Inc. Houma, Louisiana

Sheet $\frac{1}{2}$ of $\frac{2}{2}$

File No. 80-173

Date 11/03/80

Tech. Chenevert

	FIEL	D DATA	LA	SORAT	ORY	DATA		Boring Advance Method:
Dept	h t)	D DATA Standard Penetration Test (blows/foot) or Penetrameter(P) (tone/eq.ft)	Compressive Birrength (Yons/sq.ft.)	Moistere Content (*/e)	Ory Density (Ibs./os.ft.)	Liquid Limit (%)	Plasticity Index ("/")	Wash 0' to 50'
		1.2 (P)		·		100	5.4	Medium gray organic clay, w/wood
- 5		0.8 (P) 0.7 (P)	•	52		102	74	
		0.5 (P)	-	78		140	93	
-10	-	N.P.						Very soft dark gray organic clay(peat)
		0.1 (P) 0.1 (P)		140		218	135	
-15		0.5 (P)						Very soft gray clay, w/traces of organic matter
		0.2 (P)		37		66	37	
-20		0.7 (P)						
- 25		0.6 (P)						Soft gray clay, w/roots
- 30		0.1 (P)		50		77	42	very soft
- 35								
40		1.1 (P)		31				Medium gray silty clay, w/sand traces

Standard. Penetration Teet 140 lb. hommer-30°fall

Undisturbed Sample Sin, dia, Shelby Tube

No Recovery

Compressive Strength from Unconfined Compression Test
Unless Noted Otherwise
Strata Boundaries May Not Se Exact



SOIL TESTING ENGINEERS, INC.

SOIL BORING LOG project Delta Disposal Pit Boring No. B-1 Houma, Louisiana File No. 80-173 Sheet $\frac{2}{}$ of $\frac{2}{}$ Client T. Baker Smith & Sons, Inc. Date 11/03/80 Houma, Louisiana Tech Chenevert DATA FIELD LABORATORY DATA Compressive Strength (fons/eq.ft.) Moisture Content (9/s) Dry Density (1be./bu.ft.) Standard Penetration Tes (blows/foot) or Penetrameter(P) Liguid Limit (%) Plasticity Index (*/*) Depth Depth (feet) {tons/eq.ft} Soft gray silty clay, w/sand traces 0.6 (P)45 0.5(P)38 38 14 - 50 Boring terminated @ 50' PARROL Stendard Benefration Test 140 lb. hanner - 30" fall Undisturbed Sample Bin. dia Shelby Tube

No Recovery

Conpressive Strongth from Unconfined Compression Test
Miles Noted Otherwise
Straig Boundaries May Not Be Exact

SOIL TESTING ENGINEERS, INC.

project Delta Disposal Pit Houma, Louisiana

SOIL BORING LOG

Boring No. B-2

client

T. Baker Smith & Sons, Inc. Houma, Louisiana

Sheet $\frac{1}{2}$ of $\frac{2}{2}$

File No. 80-173

Date 11/04/80

Tech A. Kahn

	FIE	LD DATA	LAB	ORAT	ORY	DATA		Boring Advance Method:
	epth (feet)	Standord Penetration Test (blows/foot) or Penetrometer(P) (fone/sq.ft)	Comprise live Strength (fors/sq.ft.)	Moisters Content (*/e)	Dry Denaily (Ibs./ou.ft.)	Liquid Limit (%)	Plasticity Index (°/e)	Auger 0' to 2' Wash 2' to 50'
V V		1.2 (P)		41		107	68	Medium gray organic clay, w/some wood
		0.7 (P)		54		101	54	
-	- 5 -	0.6 (P)						
		N.P.						
F	10 -	_0.3 (P)		131		154	107	Very soft dark gray organic clay (peat)
-	n ₁ '2	0.3 (P)						
		0.4 (P)		110		284	162	
-	15 -	_O.5 (P)						Soft gray clay, w/traces of organic matter
-		0.2 (P)						
	20 —	1.2 (P)		39		88	60	·
1	25 –	0.5 (P)						Soft gray clay, w/wood & roots
	-30 -	0.4 (P)	·					
	235 -	0.1 (p)		35		63	38	very soft
	40	0.3 (P)						Soft gray silty clay, w/sand traces

Pandord Penetration Teet
130 ib. hommer-20" tall

Undisturbed Sample 31s. dia Shelby Tebe

Water Level After 10 minutes Prior to Wosh Boring)

Smittative Strangth from Unconfined Compression Test
Unises Noted Otherwise Mittel Boundaries May Not Be Exact



- SOIL TESTING ENGINEERS, INC .-

SOIL BORING LOG Project Delta Disposal Pit Houma, Louisiana

Boring No. B-2

File No. 80-173

Date 11/04/80

Tech. Chenevert

T. Baker Smith & Sons, Inc. Client

Sheet _2_ of _2

Houma, Louisiana

FIELD DATA LABORATORY DATA Moisture Content (*/o) Dry Density (ibs./ou.ft.) Standard Penetrution Test (blows/foot) or Penetrometer(P) Depth (feet) (tone/eq.ft) Soft gray silty clay, w/sand traces 0.3 (P) 35 9 32 45 0.7(P). 50 Boring terminated @ 50'

HASOL Standard Penetration Test 140 lb. hommer-50° fall

> Undisturbed Sample 3 in. dia, Shelby Tube

Compressive Strength from Unconfined Compression Test
Unless Noted Otherwise Strate Boundaries May Not Be Exact



SOIL TESTING ENGINEERS, INC.

Houma, I	sposal Pit	RING WELL JG	
el'est in Datas	Duisiana .		File No. 80-173
client T. Baker	Smith & Sons, Inc.		Date11/03/80
	ouisiana		By Chenevert
FIELD DATA	etratum Test	Drill Rig	: 200
(feet) Bangironeier	Wosh 0° to 12°	Driller:	James Kelly
		·	Monitoring Well Data
		_	Well Mo. 1
5	SEE BORING B-1		41 Top
· ·			
			G Surface
10			5 Bor. dia. (")
		nd 000 only 4ng 000 100 100 100 100 day 000 day 000 day 000 day 100 day 000 day 000 day 000 day 000 day 000 day	
	Boring terminated @	12'	
			7.751 Pellets
			8.5' sand
			Well Screen 3 Dia. (")
			3 tgth. (')
			13 Bottom
			,
	natration That or 3G in tall		•
Undisturbed 3 m des the	Sample		
No Passery		, .	
<u> </u>			
	informations and the result.		
	SOIL TESTIN	G ENGINEERS, INC	

MONITORING WELL LOG

Delta Disposal Pit Project Houma, Louisiana

Client T. Baker Smith & Sons, Inc. File No. 80-173 Date 11/04/80


н	ouma, Louisiana		Sy Chenevert
	Stendard Paretration Test (0+out / fact)	Soring Advance Method Drill R:	a- 200
DEPTH	(Blows / foot) or Panetrometer (P) - Tarvena (T) (rom / sq. fs.)	1 w . 01 to 201	James Kelly
		·	Monitoring Well Data
		-	Well No. 2
5 -		SEE BORING B-2	3
			0 Surface
10			5 Bor. dia. (")
15			15.5'Pellets
			16.0'sand Well Screen
- 20		Boring terminated @ 20'	3 Dia. (") 3 Lgth. (') 20' Bottom
		·	20 Bottom
	·		
W T	Standard Panetration Tool		
	140 % hammer 30 in felli Undeturbed Semple 3 in die Shelliy Yabe		
N	he Receivery		
צו			
	ete baunderies inferred and may nel	SOIL TESTING ENGINEERS, INC	·

SOIL TESTING ENGINEERS, INC.

TABLE I

CHEMICAL ANALYSIS

Boring No.	Depth (feet)	рн
1	2.0 to 4	7.3
1	6.0 to 8	7.9
1	10.0 to 12	5.9
1	16.0 to 18	7.3
1	28.0 to 30	8.2
1	38.0 to 40	8.1
2	0 to 2	6.8
2 2 . 2	4.0 to 6 8.0 to 10 12.0 to 14	7.7 7.5 6.3
2	18.0 to 20	8.0
2	33.0 to 35	8.0
2	43.0 to 45	8.0




Raw Data Point
 Best Fit Linear Regression
 in Stable Range

Cy = Coeff. of Consolidation \(\Delta = \text{Change in Void Ratio} \) \(\Delta = \text{Change in Pressure} \) \(\gamma = \text{Unit Weight of Water} \)

 $k = 4.3 \times 10^{-8}$ cm/sec at $e_0 = 2.45$

PERMEABILITY DETERMINED BY CONSOLIDATION TEST



 $k = 1.2 \times 10^{-7}$ cm/sec at $e_0 = 7.62$

PERMEABILITY DETERMINED BY CONSOLIDATION TEST